



## ENTRANCE SPECIFICATION SHEET

**Application for Entrance Permit Number: 2021-019 (entrance a)**  
**Applicant's Name: [REDACTED]**  
**Tay Valley Township Road: CROZIER ROAD**  
**Lot 3, Concession 1, Geographic TAY VALLEY TOWNSHIP**  
**Entrance Type: SINGLE RESIDENTIAL**

Culverts shall be **new**: (Select one of the culverts listed below)

1. HDPE (Polyethylene) corrugated pipe 210 KPa stiffness **or**
2. CSP (Steel) corrugated pipe, minimum 1.6 mm thickness
  - All culverts should have a minimum of 300 mm cover material. All culverts need to have compaction of bedding, side and cover material for lateral support of pipe. All bedding and cover material shall be Granular "A" / "M" material.
  - No curb or headwall shall extend above the surface of the roadway shoulder within a distance of four (4) meters from the edge of the traveled roadway.
  - Finished top of the entrance shall be compacted Granular "A" / "M" material.

Finished Entrance Width	Depth from Ditch to Top of Entrance	Length of Culvert Required	Culvert Diameter	Fill / Cut
5 meters	3 meter	15 meters	400 mm	FILL

**APPROVED ENTRANCE LOCATION: 5 m East of pin# 405 and 31 m West of pin #410**

**CONDITIONS OF THIS ENTRANCE:**

**MAINTENANCE OF ENTRANCE:**  
 Residents having access to a Township Road are fully responsible for the maintenance of the entrance to their property. Maintenance includes, but is not limited to, the removal of snow and ice, shoulder gravel and winter sand. During the winter, the Township will not clear entrance culverts that have become blocked as a result of improper snow disposal by the resident. Culverts that collapse deteriorate or become unsuitable for proper drainage shall be replaced by the property owner at their expense.

**Your approved entrance specification is indicated above.**  
 Changes must be approved by Tay Valley Township Public Works Department.